







Expand your business with the DS820A -- it's more than a portrait printer!



Profitable

The DS820A is a low investment, yet high-yield asset that offers photo professionals the ability to print an array of sizes from 4x8 to 8x12 and panoramic at competitive media prices. Due to the simple dye-sublimation transfer method and roll-fed design, the printer can be operated for extended periods with no downtime.



Multiple Formats

Offering a choice of high or standard density and high speed or high quality resolution, the DS820A prints from 4x8" to stunning **8x32" panoramic photos**. There's no other printer in this class that can match the performance and quality of the DS820A.



Reliable

Equipped with improved heat dissipation for higher throughput and standby mode for decreased energy consumption, as well as a **3-year Advance Exchange (AE) Extended Warranty**—an end user support program*. The DS820A can easily be shipped or transported to any event and saves valuable workspace and can be stacked for high volume printing locations.



The latest generation of print technology means image quality you can count on. The DS820A offers watermarked media on the back. The roll design allows for large amounts of media to be stored on a single roll of paper – the DS820A can print 130 8x10" photos before a new roll is required.

Specifications

Print method	Dye-subl	imation :	thermal tr	ansfer meth	nod		
Print mode		High-speed			High-quality		
Resolution			30	0x300dpi	300x600dpi	High-density	
Print size	4"x8"	6"x8"	8"x10"	8"x18"	8"x26"		
	5"x8"	8"x8"	8"x12"	8"x22"*	8"x32"		
Print number	8"x10"	130					
	8"x12"	110					
Print speed	8"x10" I	Pure Prei	mium 29	.3sec.	40.5sec.	53.5sec.	
	8"x12"	Pure Prei	mium 33	.9sec.	47.3sec.	62.8sec.	
Finishing options		Glo	ssy, Luste	er, Matte, F	ine Matte		
Ribbon finish	YMC + overcoat						
Interface		US	B 2.0				
Driver software	Windows 7, 8, 10 · MAC OS 10.8 and up						
External dimensions	12.7"Wx14.4"Dx6.7"H						
Weight (Excluding access	ories and m	edia) App	orox. 30 lb)S			
Power supply			AC100V ~ 240V 50/60 HZ				
Power consumption (when printing)		g) 100	100V / 3.96A 240V / 1.6A (Maximum) Standby 0.5W or less**				
Accessories		6' power cable, 6' USB cable, plastic print catcher,					
		prir	iter cleani	ng kit, quic	k reference card, printo	er warranty	
Media			DS820(8x12) PP, DS820(8x10)PP,				
* 0-1							

^{*} Only with 8x12 media

The DS820A offers four different finishes—Fine Matte, Matte, Luster, & Glossy!















^{*} Transition Time to power-saving Standby mode: Default 10 minutes